

SPS-CIP SERIES

for Cosmetic and Bio-Pharmaceutical Applications

DESIGN ADVANTAGES

- Designed for use with CIP cleaning systems
- Powerful suction for viscous products
- Low pulsation for smooth, consistent flows
- Low shear for fragile and shear sensitive products
- Single shaft for simple, economical maintenance
- Replaceable wear parts for maintenance in the field
- EHEDG certified

TYPICAL APPLICATIONS

- Lotions, Creams
- Conditioners, Shampoos
- Toothpaste
- Gels, Ointments, Syrups
- Crystalline Emulsions, Extracts



SPS-CIP SERIES SPECIFICATIONS								
Model	Displacement per Revolution Gallons - Liters	Max Speed	Pressure to PSI - Bar	Capacity GPM - M3/HR	Particulate Size to Inches - MM	Inlet Outlet	Temp Range °F - °C	Weight LB - KG
SPS2-CIP	.03 GAL (.11 liters)	600 RPM	217 PSI (15 BAR)	18 GPM (4.1 M3/HR)	.25 IN (6.5 MM)	2"	-40F (-40C) TO 212F (100C)	33 LB (15 KG)
SPS3-CIP	.12 GAL (.45 liters)			74 GPM (16.8 M3/HR)	.75 IN (19 MM)	3"		
SPS4-CIP	.28 GAL (1.05 liters)			168 GPM (38.1 M3/HR)	2 IN (50 MM)	4"		